






TECHNICAL SPECIFICATIONS



Category	AGITATOR-PUMP with immersed vertical axis.
Windings	Single-phase motor. Insulation Class F.
Motor body	PA66 30% glass fiber plastic shell motor housing.
Protection	IP 31 ingress protection rating.
Safety	Built-in thermal motor protection system.
Ball bearings	Ø 8 mm NSK, SKF or equivalent, in semi-rigid noise-damping silicone casing.
Motor shaft	AISI 303 INOX steel Ø 8 mm.
Fastening parts	INOX steel or corrosion-resistant materials.
Motor parts	Thermoplastic motor parts resistant to high temperature.
Cooling system	Air cooled pump with a suction speed of 1,6 m/s.
Water connection	Compatible with John Guest fittings.
Operation	Power supply 115 or 220-240 Volts - 24 hours a day non stop. Clean non drinkable water only.
Regulations	Complying with EN60335-2-41:2003/A2:2010 and WEEE/RoHs directives.
Note	Italian PATENTED component. Read the instruction booklet for correct set up and use. Designed for industrial use with CE certified cooler machinery only. Not intended for food contact.



AVAILABLE FIXING PLATES



TYPE	Volt	Hz	Amp	Watt (in)	RPM	A	B	C	Ø OUT	Propeller Ø [mm]	Weight [Kg]
MID-4	220-240	50	0,57	57	2800	96	153	64	9,5	50x15° 2 Blades	1,7
MID-7	220-240	50	0,60	64	2750	96	187	78	9,5	50x15° 2 Blades	1,8
MID-7c	220-240	50	0,60	64	2750	96	153	78	9,5	50x15° 2 Blades	1,7
MID-8	220-240	50	0,60	68	2700	96	220	90	9,5/12,3	50x15° 2 Blades	1,8
MID-5	115	60	1,25	66	3400	96	185	64	9,5	45x15° 2 Blades	1,7
MID-5	220	60	0,56	66	3400	96	185	64	9,5	45x15° 2 Blades	1,7
MID-6	115	60	1,40	70	3400	96	185	78	9,5/12,3	45x15° 2 Blades	1,8